

FE-5030
Simply closer.

Name:	Item-no:	EAN code:
FE-5030 Aquamarine Blue	N3835092	4 545350 02780-3
FE-5030 Indium Grey	N3833592	4 545350 02727-8
FE-5030 Flamingo Pink	N3834992	4 545350 02777-3
FE-5030 Pure White	N3833692	4 545350 02730-8

Main information

- 5x wide optical zoom (26-130mm*)
- Dual Image Stabilisation
- 14 Megapixels
- iAuto mode
- Advanced Face Detection
- 6.9cm/ 2.7" LCD
- AF-Tracking
- Magic Filters
- Double-Layered Crystal Shell
- Movie recording with sound
- USB-Battery Charge
- TruePic III image processor
- In-camera help guide

Several new cameras in a kaleidoscopic range of colours join the Olympus FE series. Perfect for quality hounds on a budget, the 14 Megapixel models are jam packed with technology. But that doesn't mean they are difficult to use: these beauties make capturing great shots easy. For example, AF tracking keeps moving subjects in focus, while i-Auto mode automatically identifies five commonly-encountered types of scenes and adjusts settings accordingly. Advanced Face Detection Technology and the artistic Magic Filters are also on hand. With up to 5x wide optical zoom, panorama and distance shots are a cinch. An SD card slot means worries about space are a thing of the past. Some of the models come with a practical USB charger and all are available in a range of colours that are especially brilliant thanks to a Double-Layered Crystal Shell finish.

Specifications**Image Sensor**

Effective pixels	14 Megapixels
Filter array	Primary colour filter (RGB)
Full resolution	14.5 Megapixels
Type	1/2.33 " CCD sensor

Lens

Optical zoom	5 x (WIDE)
Focal length	4.7 - 23.5 mm
Focal length (equiv. 35mm)	26 - 130 mm
Maximum aperture	2.8 - 6.5
Structure	7 lenses / 5 groups
Aspherical glass elements	5

Digital Zoom

Enlargement factor	4 x / 20 x combined with optical zoom
--------------------	---------------------------------------

LCD

Resolution	230,000 dots
Monitor size	6.9 cm / 2.7 "
LCD type	TFT
Frame assistance	Yes
Brightness adjustment	2 levels

Focusing System

Method	TTL iESP auto focus with contrast detection
Modes	
Standard mode	0.6m - ? (wide) / 1.0m - ? (tele)
Makro mode	0.15m - ? (wide) / 0.6m - ? (tele)
Super Macro mode	Closest focusing distance: 7 cm

Light Metering

Modes

Exposure System

Shutter speed	1/4 - 1/2000 s / Enhancement functionMechanical Image Stabilizer Shadow Adjustment Technology Advanced Face Detection Technology
Exposure compensation Modes	+/- 2 EV / 1/3 steps

Sensitivity

Auto	AUTO / High AUTO
Manual	ISO 64, 100, 200, 400, 800, 1600, 3200

Scene Modes

Number of scene modes Modes	14
--------------------------------	----

White Balance

AUTO WB system Preset values	Yes
---------------------------------	-----

Internal Flash

Working range (wide)	5.4 m (ISO 1000)
Working range (tele)	2.3 m (ISO 1000)

Memory

Internal memory	46 MB
Removable Media	SD / SDHC

Image Processing

Engine	TruePic III
Pixel mapping	Yes
Noise reduction	Yes
Shading compensation	Yes
Distortion compensation	Yes

Function Processing

Panorama	Yes
----------	-----

Image Editing

Black & White	No
Sepia	No
Resize	Yes
Trimming	Yes
Red-eye reduction	Yes
Shadow Adjustment	Yes

View Images

Modes	
Index	4x3 / 6x5 frames
Zoom	1.1 - 10 x
Auto rotation	Yes
Image protect mode	Yes

View Movie

Frame by frame	Yes
Fast forward	Yes
Reverse playback	Yes

Still Image Recording

DCF	Yes
EXIF	2.21
PIM	III
DPS	PictBridge
DPOF	Yes

Movie Recording System

Recording format	AVI Motion JPEG®		
Movie quality	640 x 480 / 30 fps	Recording time:	no limit
	320 x 240 / 30 fps	Recording time:	no limit
	Note: maximum file size 2GB		

Image Size

14M	4288 x 3216
8M	3264 x 2448
5M	2560 x 1920
3M	2048 x 1536
2M	1600 x 1200
1M	1280 x 960
VGA	640 x 480
16:9	1920 x 1080

Other Features

Perfect Shot Preview	Yes
Self timer	2 / 12 s
Menu guide	Yes

Interface

DC input	Yes	(CB-MA3 required)
Combined A/V & USB output	Yes	
USB 2.0 High Speed	Yes	

Menu

Menu languages in camera	39
--------------------------	----

Power Supply

Battery	LI-42B	Lithium-Ion Battery
Internal Charging	Yes	

Size

Dimensions (W x H x D)	94.1 x 55.8 x 19.9 mm
Weight	124 g (including battery and memory card)

Box Contents

- LI-42B Lithium-Ion Battery
- F-2AC AC Adapter
- CB-USB6 USB Cable
- CB-AVC3 Audio/Video cable
- Handstrap
- World Wide Warranty Card
- Instruction Manual
- [ib] Image Management Software

Battery

- LI-42B Rechargeable Lithium-Ion Battery

Charger

- LI-41C Charger

Power Supply

- F-1AC AC Adapter
- CB-MA1 DC-Jack adapter cable
- CB-MA3 DC-Jack adapter cable
- D-7 AC AC Adapter

Cables & Adapters

- CB-USB7 USB Cable
- CB-AVC5 Audio/Video cable

Case & Strap

- Leather Case FE Slim
- Neckstrap Silver