

HL-5350DNLT

TN3230/ TN3280/ DR3200



Network Ready Mono Laser Printer with Double-sided Printing



Copy

For office workgroups, this is one of the most efficient printers around. It's fast at 30 pages per minute, reduces paper costs with double-sided printing as standard and its versatile lower paper tray gives you added options – for example, use it solely for letterheads or invoices – or an extra 250 sheet capacity.

Catalogue Spec

- Ideal office printer with additional lower tray as standard
- Fast 30 pages per minute printing
- Network ready enabling a workgroup of people to share saving money on multiple devices
- Save on paper cost with double sided printing as standard
- Cost saving separate drum and toner
- High yield toner option offering even more cost effective printing
- Time saving 500 sheet paper capacity
- Optional paper tray boost paper capacity to 750 sheets
- 12 months warranty and lifetime technical support
- Energy Star certified meaning low energy usage

Detailed Spec

General

Technology	Electrophotographic Laser Printer
Class 1 Laser Product	IEC60825-1+A2:2001
Processor	NEC VR5500 300MHz
Print Speed – Standard (A4)	30 pages per minute
Print Speed – Duplex (A4)	13 sides per minute (6.5 sheets per minute)
Resolution	1,200 x 1,200dpi & 600 x 600dpi
Memory	32MB (Expandable up to 544MB, using industry standard 1 x SO-DIMM (144 PIN) slot)
First Print Out Time	Less than 8.5 seconds from ready mode
Warm-up Time	Less than 18 seconds from sleep mode
Print Language	PCL®6, BR-Script3 (Postscript®3 Language Emulation), IBM Proprinter XL, Epson FX-850

Interface	Hi-Speed USB 2.0 & IEEE 1284 Parallel
Network	Built in 10/100 Base-TX
Network Protocols	TCP/IP (IPv4 and IPv6)
IPv4	TCP/IP, ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS name resolution, DNS Resolver, mDNS, LLNMR responder, LPR/LPD, Custom Raw Port/Port9100, IPP/IPPS, FTP Server, TELNET Server, HTTP/HTTPS server, SSL/TLS, TFTP client and server, SMTP Client, APOP,POP before SMTP, SMTP-AUTH SNMPv1/v2c/v3, ICMP, LLTD responder, WebServicesPrint,
IPv6 (Off by default),	TCP/IP, NDP, RA, DNS resolver, mDNS, LLNMR responder, LPR/LPD, Custom Raw Port/Port9100, IPP/IPPS, FTP Server, TELNET Server, HTTP/HTTPS server, SSL/TLS, TFTP client and server, SMTP Client, APOP,POP before SMTP, SMTP-AUTH SNMPv1/v2c/v3, ICMPv6, LLTD responder, WebServicesPrint

Control Panel

LED's	There are 5 LED's, Toner, Drum, Paper, Back Cover and 3 colour Status LED
Buttons	There are 2 buttons Go, Job Cancel

Printer Driver

Windows®	Windows Vista®, Windows Server 2008 (32 & 64 bit editions), Windows® XP Home Edition, Windows® XP Professional (32 & 64 bit editions), Windows® Server 2003 (32 & 64 bit editions), Windows® 2000
Macintosh®	Macintosh Printer Driver for Mac OS X 10.3.9 or greater
Linux	Linux printer driver for CUPS printing system(x86, x64 environment) Linux printer driver for LPD/LPRng printing system(x86, x64 environment)"

Printer Driver Functions

N-up Printing ††	Reduce up to 2, 4, 9, 16 or 25 A4 pages into just one A4 page
Poster Printing †	Enlarge 1 A4 page into a poster using 4, 9, 16 or 25 A4 pages
Watermark Printing †	Watermark your documents with predefined text or with your own user-defined messages
Booklet Printing †	Print documents in A5 Booklet format using manual duplex

Network Management Utilities

Embedded Web Server	Web based print management software embedded onto the HL-5350DNLT
BRAdmin Light	For Setup and basic LAN management software
Driver Deployment Wizard	Easily create print drivers for hassle free deployment over your network

Free Web Downloadable Network Management Utilities - <http://solutions.brother.com>

BRAdmin Professional 3	LAN/WAN management software
Web BRAdmin	Web based LAN/WAN management software

Paper Handling

Paper Input**	Standard Tray: 250 sheets x2 [500 sheets] Multi-Purpose Tray: 50 sheets Optional Lower Tray: 1 x 250 sheets
Paper Output**	Face Down: 150 sheets Face Up: 1 sheet
Automatic Duplex	Yes
Manual Duplex ††	Yes

Media Specifications

Media Types	Standard Tray: Plain paper, Bond Paper, Recycled Paper, Transparencies (up to 10 sheets) Multi-Purpose Tray: Plain paper, Thick Paper, Bond Paper, Recycled Paper, Envelopes, Labels, Transparencies (up to 10 sheets)
-------------	---

	Optional Tray: Thin Paper, Plain Paper, Bond Paper, Recycled Paper
Media Weights	Standard Tray: 60 – 105g/m ² Multi-Purpose Tray: 60 – 163g/m ² Optional Tray: 60 – 105g/m ²
Media Sizes	Standard Tray: A4, Letter, B5 (ISO), A5, A5 (Long Edge), B6 (ISO), A6, Executive Multi-Purpose Tray: Width (69.8 – 216mm) x Length (116 x 406.4) Optional Tray: A4, Letter, ISOB5, A5, ISOB6, Executive Duplex: A4

Supplies

Toner	TN-3230: Standard yield of Approx. 3,000 pages* TN-3280: High yield of Approx. 8,000 pages*
Drum	DR-3200: Approx. 25,000 A4 Pages (one page per job)

The frequency of replacement of consumables will vary depending on the complexity of the prints, the percentage of coverage, paper size, page per job, and the type of media. For example glossy coated paper will result in a shortened life of such supplies.

Accessories

Optional Lower Tray	LT-5300: 250 sheet paper tray (maximum 1)
Additional Memory	Expandable up to 544MB total using industry standard 144pin DIMM cards (Not available from Brother)

Dimensions & Weights

Dimensions (W x D x H)	371 x 384 x 347 mm (14.6" x 15.1" x 13.7")
Weight (W x D x H)	12.2 kg (26.9lb)
Carton dimensions	525 x 570 x 699 mm (20.7" x 22.4" x 27.5" inch)
Carton weight	19.5 kg (42.9 lb)

Power Consumption

Printing	Average 675w at 25c
Ready	Average 75w at 25c
Sleep	Average 6w at 25c

Sound Pressure Level

Printing	Less than 54 dB
Ready	Less than 35 dB

Sound Power Level

Printing	Less than 6.95B
Ready	Less than 4.8B

Environmental

Power Saving	This enables the printer to consume less energy when not in use
Toner Saving	This reduces the toner usage and helps to reduce the total cost of printer ownership
Energy Star	Yes

Duty Cycles

Recommended Monthly	500 – 3,500 pages monthly print volume
Maximum Monthly	20,000 pages monthly print volume

Contents

Toner Cartridge (Approx. 3,000 pages*)
 Drum Unit (Approx. 25,000 pages)
 Power Supply Cord
 Driver Software for Windows and Mac
 Quick Set-up Guide
 PC Interface cable **NOT** included

- * Declared yield value in accordance with ISO/IEC19752.
- ** Calculated with 80g/m² paper
- † Windows® only
- †† Windows® & Mac® only