

intimus[®] 802 CC



**1.9 x 15 mm
Cross Cut**

Operation

- On / off control automatic, via light barrier
- On / off control manual, via multi-function button
- Cutout by auto Reverse when overloaded and reversed

Equipment

- "Ready" indicator
- LEDs for paper jam, bin full or door open
- Dustproof enclosure - mounted on rollers for flexible use
- Large shelf - hinged to save space
- Telescopic sliding frame with changeable, environmentally acceptable PE bag

Technical features

- Cutters made of solid, hardened special steel

Cutting mechanism is insensitive to

Paper clips	yes
CDs / DVDs	yes
3,5" floppy disks	yes
Credit cards	yes
Passports	yes
5 1/4" disks	yes
Microfilms	yes
Identity cards	yes
Staples	yes
Lam. paper/ overhead transparencies	yes
Paper and Colour cartons	yes

Performances intimus 802 CC

Particles	1.9 x 15 mm
Shredding capacity*	35 - 40 sheets
Security level DIN 32757-1	level 4
Working width	444 mm
Cutting speed	0.30 m/sec.
Catchbasket / Volume	200 l
Noise level	75 dB(A)
Power consumption/ Supply volt.	3.9/400 kW/volt
Dimensions W/ D/ H	75/55/128 cm
Weight	185 kg

* based on 70g/m² DIN A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply. Technical changes and colour variances reserved. Issue 1/2006

