







Integrated Auto Reverse Function for easy removal of jammed paper. User friendly thanks to i-control® function control, User lock. Silentec®: innovative sound dampening principle and EcoLogic for more energy efficiency.

-  i-control® Absolute transparency of the work flow
-  Silentec® Innovative concept for noise insulation
-  EcoLogic Energy efficiency
-  DLS Dynamic Load Sensor - controlled performance

- ✓ Dustproof enclosed cabinet
- ✓ Mounted on rollers for flexible use
- ✓ Material: shock resistant plastic, wood

Technical data

Cutting size paper (mm)	0,8 x 4,5 mm
Amount of paper:	5+ users
Security level DIN 32757-1	5 / NSA
Security level DIN 66 399	P-7 / F-3
Shredding capacity 70 g/m ² :	7-8 sheets
Cutting speed 70 g/m ² (m/Sec.):	0,14 m/sec.
Cutting speed 70 g/m ² (sheets/Min.):	214 sheets/min.
Shredding capacity 80 g/m ² :	6-7 sheets
Cutting speed 80 g/m ² (m/Sec.):	0,14 m/sec.
Cutting speed 80 g/m ² (sheets/Min.):	185 sheets/min.
Working width (mm):	310 mm
DIN paper size:	A3
Catchbasket volume (l):	120 l
Catchbasket volume (sheets):	4860 sheets
Power consumption (kW):	1,8 kW
Supply voltage (Volt):	230 Volt
Noise level:	57 db(A)
Weight gross (kg):	56 kg
Weight net (kg):	47 kg
Warranty on machine (years):	2 years
Warranty on the fracture of cutting cylinders:	2 years
Width (cm):	54 cm
Depth (cm):	40 cm
Height (cm):	98 cm
Type of packaging:	2 Boxes
Packaging dimensions (L/W/H):	64/50/32 & 64/49/83 cm
Packing unit:	1



Accessories

- 999 77 PE bags
- 880 35 Shredder oil for cross-cut shredder
- 801 80 Shredder oil for cross-cut shredders (re-fill)

www.intimus.com/index.php?intimus_crypto_120_CC6_en