

RecMic USB Microphones



RecMic Series

MAKE YOUR VOICE WORK FOR YOU

Olympus RecMic USB microphones allow for accurate, configurable and fully integrated voice recording in any workplace environment.

Whether you choose the barcode scanner-compatible RecMic DR-2300, the endlessly customizable RecMic DR-2200, or the intuitive, ergonomic RecMic DR-1200, you can trust that your Olympus USB microphone will fit seamlessly into your existing workflows and business practice. The superior USB cable implemented into the ergonomic designed body will provide you with years of reliable service. RecMic USB microphones let any healthcare facility, legal practice or business increase productivity, create money-saving efficiencies and improve information security.

Features

- ▶ Real-time recording and transcription using speech recognition software
- ▶ Easily integrated with existing software, applications and workflows
- ▶ Configurable controls and functions, system-wide or for individual users
- ▶ Professional microphones guarantee ultra-clear voice data entry
- ▶ Awarded the highest level Dragon score (6) from Nuance

Use case:
Real-time data entry into EHR/EMR systems

The available **ODMS workflow software** allows RecMic USB microphones to integrate directly with speech recognition software. This, in turn, allows physicians and nurses to enter information into EHR systems in real time, without ever touching a keyboard.



RecMic Specifications

| | RecMic DR-2300 | RecMic DR-2200 | RecMic DR-1200 |
|--------------------------------------|--|--|--|
| Overall Frequency Response | 300~10,000Hz (SP) 100~14,000Hz (PCM) | 300~10,000Hz (SP) 100~14,000Hz (PCM) | 300~10,000Hz (SP) 100~14,000Hz (PCM) |
| Microphone Sensitivity | -37dBv | -37dBv | -37dBv |
| Microphone Sensitivity Difference | Variable or 0/+6/+18dB (Selectable from SDK) | Variable or 0/+6/+18dB (Selectable from SDK) | Variable or 0/+6/+18dB (Selectable from SDK) |
| Maximum Output | 320mW | 320mW | 320mW |
| Microphone/Speaker Diameter | 10mm/28mm | 10mm/28mm | 10mm/28mm |
| Input Level | +86dB SPL(-45dBv) | +86dB SPL(-45dBv) | +86dB SPL(-45dBv) |
| Cord Length | 98.4 inch (2.5m) | 98.4 inch (2.5m) | 98.4 inch (2.5m) |
| Dimensions | 6.1x1.8x1.2 inch (154x44.6x31.6 mm) | 6.1x1.8x1.2 inch (154x44.6x31.6 mm) | 6.1x1.8x1.2 inch (154x44.6x31.6 mm) |
| Weight | 7.3oz (206g) | 7.1oz (201g) | 7.1oz (201g) |
| Voice Recognition Compatible | Yes | Yes | Yes |
| SC-1 Barcode Scanner Compatible | Yes | No | No |
| Dragon® Certified | Highest Dragon Rating | Highest Dragon Rating | Highest Dragon Rating |
| Main Recording Controls | Precise Slide Switch | Precise Slide Switch | Intuitive Push Button |
| Supported Computer Operating Systems | Windows (XP, Vista, 7, 8) Mac OS X (10.4.11-10.8) | Windows (XP, Vista, 7, 8) Mac OS X (10.4.11-10.8) | Windows (XP, Vista, 7, 8) Mac OS X (10.4.11-10.8) |
| Central Management | Yes | Yes | Yes |
| Package Contents | RecMic DR-2300 Warranty Card Instruction Manual | RecMic DR-2200 Warranty Card Instruction Manual | RecMic DR-1200 Warranty Card Instruction Manual |
| Configuration/Customization Software | Device Configuration Manager Software Development Kit RecMic Administration Center | Device Configuration Manager Software Development Kit RecMic Administration Center | Device Configuration Manager Software Development Kit RecMic Administration Center |



RECMIC DR-2300 WITH SC-1 BARCODE SCANNER

**Secure.
Reliable.
Integrated.**

RecMic USB microphones from Olympus capture crystal-clear sound and integrate it directly with existing workflows and processes.



OLYMPUS

